

Tipping kit to suit a Truck with an 18 Speed Roadranger Gearbox and a 5m tipping Body

## Tipping Kit Inclusions



3 Stage Cylinder  
Displacement Type  
Hard Chromed  
Mounting Brackets incl.

Lifts 28t to 51° over a 300mm Overhang.

P/N: S2-55BT-3-4200

18 Speed Roadranger combination  
250 Nm PTO torque  
65 Lpm @ 1000rpm Pump  
Cont: 3200 psi, 1800 rpm  
P/N: PPK-HCAR




120 Lpm tip valve  
Pneumatic control  
2500 psi relief setting  
Max: 4000 psi  
P/N: OP20W1/TM



Pneumatic Cab Control  
6mm Nylon air fittings  
PTO engagement switch  
Serviceable parts  
P/N: AFH-400-03-332



90L steel oil tank  
2 Port Options 1-1/4" BSPP c/w Plug  
Bolt on inspection plate  
Filler Breather & Site Glass  
Provision for filtration  
P/N: ACC-T90L



25 Micron return line filter  
Tank top mounted c/w male nipple  
300 Lpm  
Paper Element  
P/N: RTIR-10-25



1-3/4" Rear Hinge Kit  
2x Chassis Brackets  
4x Body Brackets  
Collars, grease nipples and bar  
P/N: HG1-3/4



6 Line Nylon air kit  
Air fittings  
Suction Elbow  
Port fitting adaptors



Note:  
Surcharge Options include alloy oil tank, 160 Lpm tip valve,  
PTO variation and additional air switch.

NZ 0800 22 55 69  
AU 1800 22 55 69  
[www.transporthydraulics.com](http://www.transporthydraulics.com)  
[sales@transporthydraulics.com](mailto:sales@transporthydraulics.com)

Quote Ref:  
Date:  
NZ\$



INNOVATION IN MOTION

[www.transporthydraulics.com](http://www.transporthydraulics.com)

